

Part Number	Description	Tube Wall Thickness		Braid OD Nominal		Tolerance +/-		Braid ID Nominal		Tolerance +/-		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius	
		(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(psi)	(bar)	(psi)	(bar)	(mm)	(in)
N900-04	1/4" Light Weight HP	1.03	0.041	9.53	0.375	0.38	0.015	5.64	0.222	0.25	0.010	5,000	345	16,000	1,103	38	1.50
N900-06	3/8" Light Weight HP	1.03	0.041	12.01	0.473	0.38	0.015	7.82	0.038	0.25	0.010	5,000	345	16,000	1,103	64	2.50
N900-08	1/2" Light Weight HP	1.17	0.046	15.24	0.600	0.44	0.018	10.19	0.401	0.25	0.010	5,000	345	16,000	1,103	74	2.90
N900-10	5/8" Light Weight HP	1.30	0.051	18.03	0.710	0.46	0.018	12.57	0.495	0.25	0.010	5,000	345	16,000	1,103	84	3.30
N900-12	3/4" Light Weight HP	1.30	0.051	24.64	0.970	0.51	0.020	15.67	0.617	0.38	0.015	5,000	345	16,000	1,103	102	4.00
N900-16	1" Light Weight HP	1.30	0.051	31.75	1.250	0.51	0.020	22.02	0.867	0.37	0.015	5,000	345	16,000	1,103	127	5.00
N900-20	1-1/4" Light Weight HP	1.80	0.071	40.64	1.600	1.02	0.040	28.58	1.125	0.64	0.025	4,000	276	16,000	1,103	305	12.00
N900-24	1-1/2" Light Weight HP	1.80	0.071	48.77	1.920	1.02	0.040	34.93	1.375	0.64	0.025	4,000	276	12,000	827	356	14.00