



Final Crimp Specifications

For PTFE Smooth Bore Fittings

**FOR FITTING PART NUMBERS STARTING WITH
PP-100, PP-110 & PP-120**

Wall Thickness	Hose Size	Crimp Spec. Inches	Crimp Die
.40	-03	.300-.305	7mm
.30	-04	.350-.355	7mm
.30	-05	.404-.409	8mm
.30	-06	.478-.482	10mm
.30	-08	.568-.573	14mm
.30	-10	.673-.678	16mm
.30	-12	.800-.805	16mm
.30	-16	1.044-1.049	26mm



FOR TWO PIECE FITTINGS STARTING WITH BRFJ, BRPB, CSFJ, CSPB, SSFJ AND SSPB

Wall Thickness	Hose Size	Crimp Spec. Inches	Crimp Die
.40	-03	.306-.310	7mm
.30	-04	.365-.369	7mm
.30	-05	.451-.455	8mm
.30	-06	.516-.520	10mm
.30	-08	.612-.616	14mm
.30	-10	.722-.726	16mm
.30	-12	.880-.886	16mm
.30	-16	1.194	26mm



- HAVE QUESTIONS ABOUT CRIMPING?
VISIT OUR YOUTUBE CHANNEL
LOCATED ON THE HOME PAGE
- OR GIVE US A CALL

PARAGON

PERFORMANCE



THE ORIGINAL SINCE 1997

455 w. Century Ave. Suite A

San Bernardino, CA 92408